


# AENOR

## EC-Type Examination Certificate Directive on Marine Equipment



**B17/000001**

In compliance with 2014/90/EU Directive, the notified body AENOR (n° 0099) has issued this certificate to

### **GARNICA PLYWOOD VALENCIA DE DON JUAN, S.L.**

Registered office	CR DE VILLAFER, KM 2 24200 VALENCIA DE DON JUAN (Leon - España)
Product	Surface materials and floor coverings with low flamespread characteristics. Plywood board.
Directive	2014/90/UE, Reglamento de ejecución (UE) 2018/773 2014/90/EU, Commission Implementing Regulation (EU) 2018/773
References	See annex for more information.
Production site	CR DE VILLAFER, KM 2 24200 VALENCIA DE DON JUAN (Leon - España)
Certification scheme	In order to issue this EC type-examination certificate, AENOR has performed the appropriate examinations and tests indicated in Module B Annex II of the 2014/90/EU Directive on Marine Equipment
	This certificate supersedes B17/000001, dated 2016-04-29
First issued on	2016-04-29
Modified on	2021-04-29
Validity date	2026-04-29

Rafael GARCÍA MEIRO  
Chief Executive Officer

Original Electronic Certificate

# AENOR

## EC-Type Examination Certificate Directive on Marine Equipment

B17/000001

### Annex to Certificate

SOLAS 74 Rules, as amended, and relevant IMO resolutions and circulars	Reg. II-2/3, Reg. II-2/5, Reg. II-2/6, Reg. X/3, Res. OMI MSC.36 (63)-(Código NGV 1994) 7, Res. OMI MSC.97 (73)-(Código NGV 2000) 7, OMI MSC/Circ.1120
Test standards	Res. OMI MSC.307 (88)- (Código PEF 2010), in its amended version
Annex A.1 MED item Chapter 3	MED/3.18. Surfaces and floor coverings with low flame spread characteristics, a) decorative wood veneer, c) floor coverings
Tests carried out	PEF 2010 Code. Part 5 and Annex 2 ítem 2.2 y 2.3
Test reports	055407 M1 (2016-02-09)
Substrate applied for the test	Thick Steel
Product description	Plywood board made of glued veneer, impregnated with inorganic salts
Reference	Fireshield Marine Nautic
Minimum/maximum thickness	3-21,5 mm
Specie	Poplar (populus spp.)
Colour	Light brown (Natural wood)
Density	440 - 500 kg/m <sup>3</sup>
Impregnate Product	Aqueous solution of inorganic salts
Impregnation Conditions	120 kg/m <sup>3</sup>
Approval limitations	Approved for use as a surface and floor covering with low flame spread characteristics It can be applied on any floor covering with low flame spread, steel, or non-combustible material
Nº Veneers	3-5-7-9-11
First issued on	2016-04-29
Modified on	2021-04-29
Validity date	2026-04-29